



KUNKLE MODEL 930 SAFETY VALVES

SAFETY AND RELIEF PRODUCTS

High capacity cast iron safety valve that meets ASME section IV steam standard 'HV' and is National Board certified



FEATURES

- Extra high capacity for industrial, commercial and residential low pressure steam heating boilers.
- Cast iron body with bronze nozzle, disc and guide.
- Large seat area/guide area ratio and disc pivot design ensures optimum performance.
- Seats are lapped for optimum performance.
- Reversible lift lever for 'pull-up' or 'pull-down' manual testing.
- All adjustments factory sealed to prevent tampering or disassembly.
- Tested and inspected for pressure setting and leakage.

GENERAL APPLICATION

Model 930 is suitable for use on low pressure steam heating boilers to ASME code section IV at 15 psig set pressure.

TECHNICAL DATA

Sizes: 2", 2½", 3"
Connections: Threaded NPT
Temperature: 250°F (121°C)
Pressure: 15 psig (1 barg) only
Code: ASME IV



KUNKLE MODEL 930 SAFETY VALVES

SAFETY AND RELIEF PRODUCTS

PARTS AND MATERIALS

No.	Part name	Materials
1	Set screw	SS
2	Nozzle	BRZ B584-C84400 or BRS B283-C48500
3	Disc	BRZ B584-C84400
4	Body	Cast Iron, A126 class A or B1
5	Step spring	Brass B16
6	Snap ring	SS, A151
7	Wire and seal	SS wire and lead seal
8	Spring	Steel, A231 aluminum coated
9 ^[3]	Compression screw guide	BRZ B584-C84400
10	Lever	Steel
11	Lift washer	Brass, B16
12	Stem	SS, A582-303
13 ^[2]	Gag bracket	Aluminum, SB211-6061-T6/anodized
14 ^[2]	Threaded knob	Phenolic/stl, A108-1018 ZN PL
15 ^[2]	Washer	Stl, A108-1018 ZN PL
16 ^[2]	Retaining washer	Nylon

NOTES

1. Finish heat resistant gray primer paint.
2. Gag assembly ships with valve, not installed. Applies only to gag option.
3. Modified with 2 threaded holes for gag assembly. Applies only to gag option.

SPECIFICATIONS^[1]

Valve size ^[2]	Dimensions, in			Weight lb	Orifice area in ²	Capacity lb/h
	A	B	C			
2"	3 ¹ / ₈	3	7 ¹ / ₄	8	2.16	3164
2 ¹ / ₂ "	3 ³ / ₄	3 ¹ / ₂	8 ¹ / ₄	12	3.08	4501
3"	4 ¹ / ₄	4	8 ³ / ₄	19	4.75	6949

NOTES

Dimensions are for reference only.

1. ASME section IV steam (U.S., lb/h): set pressure = 15 psig, flow coefficient = 0.818
2. Inlet and outlet are the same size.

SELECTION GUIDE

Example: 0930 - H 01 - GC 0015

Model

0930

Inlet size

H 2"

J 2¹/₂"

K 3"

Variation

01 Catalog standard

02 With gag



