

Pressure Regulating with PP & PP5 Spring-loaded Pilot



Pressure Pilot	(Standard: 1.0 psig accuracy) (High-accuracy: 0.5 psig accuracy)	PP PP5
Pilot Body Material	Cast Steel	
Max Inlet Pressure	300 PSIG	
Reduced Outlet Pressure Range	3-200 PSIG	
Inlet Pressure Range	15-300 PSIG	
(with HD Standard main valve)		
(with HD Low-Pressure (LP) main valve)	5-20 PSIG	
Minimum Differential Pressure	10 PSI	
(with HD Standard main valve)		
(with HD Low-Pressure (LP) main valve)	3 PSI	

Typical Applications

The PP & PP5 Pressure Pilots are used with the HD Regulator to control steam pressure in steam mains or for process equipment. Pilot-operated regulators maintain constant downstream pressure even when the inlet pressure to the valve fluctuates or steam usage varies. The PP-Pressure Pilot is adequate for controlling pressure in most industrial applications. For increased accuracy use the PP5 Pilot.

PP-Pressure Pilot (Standard) 1.0 PSIG accuracy

PP5-Pressure Pilot (Special Applications) 0.5 PSIG accuracy

Features

- The PP-Pilot can maintain downstream pressure to ± 1 PSIG
- PP5-Pilot can maintain downstream pressure to ± 0.5 PSIG
- Choices of three overlapping pressure ranges
- Pilot is easily installed on pilot adapter using four bolts, no tubing connections are required
- Full port strainer and blowdown valve on pilot adapter for protection of pilot from dirt and scale
- Solid floating diaphragm is more failure resistant
- Watson McDaniel's pilots can be used with other manufacturers' regulators

HD Main Valve

with
PP-Pressure Pilot



Model Code for Main Valve: **HD-17-F150**
(2" HD Series Valve with 150# Flanges)

Model Code for Pilot: **PP-B**
(Pressure Pilot with 20-100 PSIG Range)

MATERIALS for PP Pressure Pilot

PP Pilot Body	WCb 216 Cast Steel
PP5 Pilot Body	Cast Iron
Head & Seat Gasket	302 SS
Diaphragm	Phosphor Bronze
Head & Seat Assembly	Hardened SST (55 Rc)

MATERIALS for HD Main Valve

Body	Ductile Iron
Cover	Ductile Iron
Gasket	Grafoil/Garlock
Cover Screws	Steel
Pilot Adapter	Ductile Iron/Cast Steel
Screen	Stainless Steel
Tubing	Copper
Valve Seat	Hardened SST (55 Rc)
Valve Disc	Hardened SST (55 Rc)
Diaphragm	Phosphor Bronze

Options

- Pressure pilot can be used with temperature pilot to eliminate the need for two separate regulators
- Solenoid pilot can be added for remote on/off control of regulator

Example: PP-B Pilot at 20-100 PSIG

Reduced Pressure Range PSI	Model Code	Spring Color	Weight lbs
PP-Pressure Pilot (for Standard Industrial Applications) 1.0 PSIG accuracy			
3-25	PP-Y	Yellow	10
20-100	PP-B	Blue	10
80-200	PP-R	Red	10
PP5-Pressure Pilot (Special Applications) 0.5 PSIG accuracy			
1-10	PP5-Y*	Yellow	25
10-25	PP5-B*	Blue	25

* A Spacer (model # BAP-SPACE) is required when using PP5 Pressure Pilots on a 3" & 4" HD Main Valve.

Units: inches

